

DIGITAL PRECISION GAUGE



For pressure control in gas compartments

3-558-R010/A
with 5 point certificate

3-558-R010/B
with 11 point certificate

3-558-R010/C
with DKD certificate

Indication range -1 to 10 bar / 0 - 10 bar / 0 - 1000 kPa / 0 - 145 psi

Indication in bar, kPa, psi (reversible) / class 0.1

This is a useful Temperature compensated measuring device when precise pressure indication is required.

The connecting hose for measuring devices is equipped with a self-closing coupling so that no SF₆ gas can escape into the atmosphere during the testing process. The device can be transported comfortably and safely in the handy plastic case.



Technical data:

| |
|---|
| Case dimensions: L 390 mm, W 310 mm, H 150 mm |
|---|

| |
|----------------|
| Weight: 3.5 kg |
|----------------|

Standard equipment:

| |
|--------------------------|
| Coupling tongue part DN8 |
|--------------------------|

| |
|---------------------------|
| Coupling tongue part DN20 |
|---------------------------|

| |
|---|
| Temperature compensated digital precision gauge -1 to 10 bar /class 0.1 |
|---|

| |
|---|
| 1 m long Teflon hose with connecting coupling for measuring devices |
|---|

| |
|----------------------|
| Handy transport case |
|----------------------|

| |
|------------------|
| Operating manual |
|------------------|

Optional accessories at an extra charge:

| | |
|-----------------------------|-------------|
| Additional operating manual | 6-0004-R213 |
|-----------------------------|-------------|

Other transition pieces are available on request.

Packing:

| | |
|------------------------|--------------|
| Packing for 3-558-R010 | 05-1990-R004 |
|------------------------|--------------|

