



DEVICES FOR DETERMINATION OF THE SF₆ GAS QUALITY

For precise measurement

3-032-R003

Measuring device for different decomposition products and gas residues

During the operation of gas insulated switchgear decomposition products might occur after a breakdown which has a negative impact on the gas quality in the circuit breaker as well as on the insulation properties.

For this reason the measurement of decomposition products is very important. The measurement can be carried out easily by means of test tubes and plastic bags. The following concentrations can be measured:

- » Sulphur dioxide SO₂: 1 to 500 ppm_v
- » Hydrogen fluoride HF: 1.5 to 15 ppm_v
- » Oil mist: 1 to 10 mg / m³ (0.16 to 1.6 ppm_{mass})



- The device is supplied in a handy plastic case. Gastight couplings DN8 and DN20 are also included in the scope of supply.

DEVICES FOR DETERMINATION OF THE SF₆ GAS QUALITY



3-032-R003

Measuring device for different decomposition products and gas residues

Technical data:

Dimensions: W 198 mm, H 115 mm, D 165 mm
Case dimensions: W 360 mm, H 290 mm, D 165 mm
Weight without case: 2.4 kg
Measuring principle: Chemical reaction

Standard equipment:

Measuring device for decomposition products with flowmeter and needle valve
Safety valve
Mounting for test tubes
DILLO connecting couplings in DN8 and DN20
Tube opener
Connecting piece with connecting hose
2 spare O-rings
2 m long flexible connection
Black plastic transport case
Operating manual

Optional accessories at an extra charge:

10 pieces test tubes for sulphur dioxide SO ₂ type 1/a; measuring range 1 to 25 ppm _v Plastic bags with a volume of 1 litre are needed (3-032-21)	05-1026-R001
10 pieces test tubes for sulphur dioxide SO ₂ type 20/a; measuring range 20 to 220 ppm _v Plastic bags with a volume of 1 litre are needed (3-032-21)	05-1026-R002
10 pieces test tubes for sulphur dioxide SO ₂ type 50/b; measuring range 50 to 500 ppm _v Plastic bags with a volume of 1 litre are needed (3-032-21)	05-1026-R003
10 pieces test tubes for hydrogen fluoride HF type 1.5/b; measuring range 1.5 to 15 ppm _v Plastic bags with a volume of 2 litres are needed (3-032-20)	05-1026-R010
10 pieces test tubes for detection of oil mist type 1/a; measuring range 1 to 10 mg/m ³ (0.16 to 1.6 ppm _{mass}) Plastic bags with a volume of 10 litres are needed (3-032-22)	05-1026-R015
10 pieces plastic bags with a volume of 1 litre	05-1025-R001
10 pieces plastic bags with a volume of 2 litres	05-1025-R002
3 pieces plastic bags with a volume of 10 litres	05-1025-R004
Adapter for emptying the discharge gas collecting bag	3-969-R005
Additional operating manual	6-0004-R213

Packing:

Packing for 3-032-R003	05-1990-R004
------------------------	--------------

